



S1
S2
S3

AIRCLEAN ACTIVATED CARBON ADSORBERS

The S-Series Air Purification Adsorbers are filled with high quality Service Tech activated carbon and are designed for the purification of your vapor waste or process stream.

Highly corrosive atmospheres, and waste streams require adsorber construction of material that will stand up over time. High density polyethylene canisters are designed for such applications and are available on all units.

DESIGN SPECIFICATIONS

MODEL	DIMENSIONS DIA. x HGT.	CARBON WEIGHT	INLET / OUTLET	SUGGESTED FLOW	MAX RATED FLOW
S-1*	24" x 36"	200 LBS.	2"/2"	100 CFM	125 CFM
S-2*	24" x 36"	180 LBS.	4"/4"	300 CFM	350 CFM
S-3 Poly	24" x 36"	150 LBS.	6"/6"	500 CFM	550 CFM
S-3 Steel	24" x 36"	150 LBS.	4"/4"	500 CFM	550 CFM

*Specify Polyethylene (P) or Double Epoxy lined steel (DE)

D.O.T. rated
Low pressure drop

APPLICATIONS

Soil vapor extraction
Air stripper polishing
Welding areas

Tank vents
Sewage odor control
Printing operations

S-2, S-3



S-1

