



SERVICE TECH, INC.

Activated Carbon Engineering, Sales and Service

S-3 STEEL AIRCLEAN 150 POUND ACTIVATED CARBON AIR PURIFICATION ADSORBER

The SERVICE TECH S-3 (air)
Canister handles up to 550 CFM

FEATURES


- * 150 Pounds of high activity carbon.
- * Epoxy lined steel
- * DOT rated. Acceptable for shipment of hazardous spent carbon.
- * Side drain for removal of accumulated condensate.
- * Low pressure drop.
- * PVC Internal piping.
- * High Temperature (180°F)

APPLICATIONS


- * Soil Vapor Extraction
- * Air Stripper Polishing
- * Welding Areas
- * Tank Vents
- * Sewer Odor Control
- * Printing Operations

SPECIFICATIONS

Container	- 24" dia/ x 34" hgt. - double epoxy lined steel
Carbon	- 150 lbs. virgin high activity carbon
Max. Suggested Flow	- 500 CFM
Max. Rated Flow	- 550 CFM
Shipping Weight	- 235 lbs.
Inlet	- 4" fpt
Outlet	- 4" fpt
Drain	- 2" Bung



SERVICE TECH S-3
PRESSURE DROP CURVE



(508) 673-9784 • Toll Free (800) 368-0043 • Fax (508) 673-6151

• Mailing: P.O. Box 8093, Cranston, RI 02920 • Sales & Distribution: 1658 G.A.R. Highway, Swansea, MA 02777 • Warehouse & Manufacturing: 1980 Fall River Avenue, Seekonk, MA 02771